

KILLER TOOLS & Equipment Corporation



6105 Main Ave. Suite 11, Orangevale, Ca., 95662

Phone: 800-369-4262 Fax 800-810-4513

ART38-SC assembly

1. Remove contents of carton.
2. Install casters through square hole in black base/tray and fasten with barrel nut and 5mm hex key.



3. Install right and left upright brackets using 4 60mm bolts with 1 washer, and 1 nut each bolt using a 14mm wrench.



4. Install seat using 4 Phillips screws.
5. Install yellow pull handle brackets so that pull handle angles away from seat using 4 60mm bolts, 4 washers, 4 nuts.



6. Install black 150mm connecting tubes to “U” shaped pull handle using 2 34mm bolts, 2 washers, 2 nuts.



7. Install 2 black “Z” brackets to “U” shaped pull handle using 2 20mm bolts and 2 washers.
8. Install “u” shaped pull handle into pull handle brackets so that the “Z” brackets face the seat, for proper weight distribution.



9. Make sure all fasteners are sufficiently tightened.
10. Install Killer Tools 38 series steel electrode dent puller into tray under seat, and you are ready to use.

****WARNING****

DO NOT LEAN ON OR USE PULL HANDLE AS BACK REST. This can cause the cart to tip over causing great bodily harm.